




ALL TYPES BEARINGS BUSINESS CO.,LTD.



S7012 ACD/P4A Bearing 2D drawings and 3D CAD models

60 mm x 95 mm x 18 mm SKF S7012 ACD/P4A angular contact ball bearings

Bearing No. S7012 ACD/P4A

Size	95x60x18 mm
Bore Diameter	95 mm
Outer Diameter	60 mm
Width	18 mm
d	60 mm
D	95 mm
B	18 mm
d ₁	70.8 mm
d ₂	70.8 mm
D ₂	86.74 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	27.2 mm
d _a - min.	66 mm
d _a - max.	70.2 mm
d _b - min.	66 mm
d _b - max.	70.2 mm
D _a - max.	89 mm
D _b - max.	91.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	39 kN
Basic static load rating - C ₀	33.5 kN
Fatigue load limit - P _u	1.4 kN



ALL TYPES BEARINGS BUSINESS CO.,LTD.

Limiting speed for grease lubrication	13000 r/min
Ball - D_w	11.112 mm
Ball - z	19
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	240 N
Preload class B - G_B	480 N
Preload class C - G_C	960 N
Preload class D - G_D	1920 N
Calculation factor - f	1.12
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2D}	1.08
Calculation factor - f_{HC}	1
Preload class A	168 N/micron
Preload class B	219 N/micron
Preload class C	291 N/micron
Preload class D	393 N/micron
Category	Precision Ball Bearings
Inventory	0.0
Manufacturer Name	SKF



ALL TYPES BEARINGS BUSINESS CO.,LTD.

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 7 ISO P4
Material - Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	25 Degree
Preload	None
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Enclosure Type	Non Contact Seal
Flush Ground	No
Inch - Metric	Metric
Other Features	Single Row Angular Contact High Capacity Basic Design
Long Description	60MM Bore; 95MM Outside Diameter; 18MM Width; 2 Seals Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 1 (Single) Bearing; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring R
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Ball Angular Contact
Manufacturer URL	http://www.skf.com
Width	0.709 Inch 18 Millimeter
Bore	2.362 Inch 60 Millimeter



ALL TYPES BEARINGS BUSINESS CO.,LTD.

Outside Diameter	3.74 Inch 95 Millimeter
d_1	70.8 mm
d_2	70.8 mm
D_2	86.74 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	66 mm
d_a max.	70.2 mm
d_b min.	66 mm
d_b max.	70.2 mm
D_a max.	89 mm
D_b max.	91.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	39 kN
Basic static load rating C_0	33.5 kN
Fatigue load limit P_u	1.4 kN
Attainable speed for grease lubrication	13000 r/min
Ball diameter D_w	11.112 mm
Number of balls z	19
Preload class A G_A	240 N
Static axial stiffness, preload class A	168 N/ μ m
Preload class B G_B	480 N
Static axial stiffness, preload class B	219 N/ μ m
Preload class C G_C	960 N
Static axial stiffness, preload class C	291 N/ μ m
Preload class D G_D	1920 N
Static axial stiffness, preload class D	393 N/ μ m
Calculation factor f	1.12



ALL TYPES BEARINGS BUSINESS CO.,LTD.

Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.41 kg